

Founding properties on measurement

Claudio Masolo

Laboratory for Applied Ontology, ISTC-CNR

`masolo@loa-cnr.it`

Fois 2010 – Toronto, May 11-14.

1 Predication

- $1m(x) \wedge 2m(y) \rightarrow x <_L y$
- $Red(x) \wedge Orng(y) \rightarrow x \sim_C y$
- $Red(x) \wedge Orng(y) \wedge Blue(z) \rightarrow Closer_C(x, y, z)$

2 Reification

- Length($x, 1\text{m}$) \wedge Length($y, 2\text{m}$) $\wedge 1\text{m} < 2\text{m}$

$$1\text{m}(x) \triangleq \text{Length}(x, 1\text{m})$$

$$x <_{\text{L}} y \triangleq \exists l_1 l_2 (\text{Length}(x, l_1) \wedge \text{Length}(y, l_2) \wedge l_1 < l_2)$$

- Color(x, red) \wedge Color(y, orng) $\wedge \text{red} \sim \text{orng}$

$$\text{Red}(x) \triangleq \text{Color}(x, \text{red})$$

$$x \sim_{\text{C}} y \triangleq \exists c_1 c_2 (\text{Color}(x, c_1) \wedge \text{Color}(y, c_2) \wedge c_1 \sim c_2)$$

- Not necessarily extensional: the set of objects that have lenght 1m could be identical to the set of objects that have color red.

3 A general framework

- $\mathbf{ob}(x)$: x is an object;
 - $\mathbf{tm}(t)$: t is a time;
 - $\mathbf{sp_i}(r)$: r is an region in the space \mathbf{i} ;
 - $\mathbf{L}(r, x, t)$: the region r is the **location** of the object x at time t .
-
- ▶ $\mathbf{Length}(x, 1\mathbf{m}, t) \triangleq \mathbf{sp_L}(1\mathbf{m}) \wedge \mathbf{L}(1\mathbf{m}, x, t)$
 - ▶ $\mathbf{Color}(x, \mathbf{red}, t) \triangleq \mathbf{sp_C}(\mathbf{red}) \wedge \mathbf{L}(\mathbf{red}, x, t)$
 - ▶ $x \sim_{\mathbf{C}, t} y \triangleq \exists c_1 c_2 (\mathbf{sp_C}(c_1) \wedge \mathbf{sp_C}(c_2) \wedge \mathbf{L}(c_1, x, t) \wedge \mathbf{L}(c_2, y, t) \wedge c_1 \sim c_2)$

4 Ontological neutrality

- This general framework is quite weakly characterized therefore it is compatible with different theories of properties:
 - ▶ regions as *universals*; location as *instance of* (**Universalism**);
 - ▶ regions as *classes of resembling tropes*; location as a composition of *inherence and membership* (**Trope Theory**);
 - ▶ regions as *classes of resembling objects*; location as *membership* (**Resemblance Nominalism**);

5 Towards a more empirical approach

- Is it possible to provide a more empirical or epistemic interpretation of this general framework?
- Is it possible to classify and compare objects in a **communicable** and **inter-subjective** way (allowing for useful **predictions**) without making powerful assumptions about their conformity with 'ontological properties'?

6 Giving a central role to measurement


- **Hypothesis:** an object is classified as '1m long' if and only if the result of its length measurement is 1m.
- Roughly:
 - ▶ spaces are related to measurement instruments;
 - ▶ regions in a space correspond to the values of a measurement instrument related to this space;
 - ▶ the location relation corresponds to the result of the measurement of an object by means of this instrument.

7 Towards an empirical theory of measurement

- *Representational Measurement Theory*, RMT (Suppes, Krantz, Luce, and Tversky), is one of the best known measurement theories.
- *Empirical Measurement Theory*, EMT (Frigerio, Giordani, and Mari) explicitly considers the epistemic/empirical aspect of measurement.
- I extend EMT by
 - ▶ providing a formal account of the *measurement standards* and of the *calibration* process and
 - ▶ considering time and *diachronic* comparisons.

(!) Later, I will motivate why I prefer EMT to RMT.


8 Measurement system: support



- m is the (physical) **support**
 - ▶ m is the scale in this case;
- $\mathcal{E} = \langle U, R_1, \dots, R_n \rangle$ is the **empirical structure**: the set of empirically discernible internal states of m (after any possible interaction with an object) and the relations between them
 - ▶ U is the set of 4 states $\{s_0, s_1, s_2, s_3\}$ that correspond to any alignment between the indicator and one notch (discrete scale);
 - ▶ R is the order established (in U) by the clockwise order of notches:



$$s_0 \prec s_1 \prec s_2 \prec s_3$$

9 Measurement system: symbolization



- $\mathcal{S} = \langle V, S_1, \dots, S_n \rangle$ is the **symbolic structure** necessary for abstracting from and refer to the internal states of the support m
 - ▶ $V = \{0\text{kg}, 1\text{kg}, 2\text{kg}, 3\text{kg}\}$
 - ▶ $S: 0\text{kg} < 1\text{kg} < 2\text{kg} < 3\text{kg}$
- $\lambda: U \rightarrow V$ is the **symbolization function**
 - ▶ $\lambda(s_n) = n\text{kg}$
 - ▶ $n\text{kg} < m\text{kg}$ iff $s_n \prec s_m$

10 Measurement system: interaction



- $\kappa: O \rightarrow U$ is the **interaction function** that associates to an object $o \in O$ the internal state of the complex system $m \bullet o$
 - ▶ $\kappa(o) = s_1$, then
 - ▶ $\lambda(\kappa(o)) = 1\text{kg}$


it describes as the support interacts with the environment.

11 RMT vs. EMT

- RMT conceives measurement as the building of a homomorphism from an *empirical structure* $\mathcal{O} = \langle O, R_1^O, \dots, R_n^O \rangle$ to a *numerical structure* $\mathcal{S} = \langle V, S_1, \dots, S_n \rangle$.
 - In EMT, it is the structure of the support that *induces* (via an interaction process) a structure on objects:
 - ▶ U gives the *resolution* of the MS
$$o \approx o' \text{ iff } \kappa(o) = \kappa(o')$$
 - ▶ each R_i induces a relation on objects
$$R_i^O(o_1, \dots, o_n) \text{ iff } R_i(\kappa(o_1), \dots, \kappa(o_n))$$
- i.e. an MS (and the measurement procedure) provides a specific ‘point of view’ on reality.

12 Measurement standard (mST)


- a set R of *reference objects*: $\{r_0, r_1, r_2, r_3\}$;
(in the example we have the problem of the 'null object' r_0)
- a *symbolic structure* $\mathcal{R} = \langle M, S_1^M, \dots, S_n^M \rangle$;
 - ▶ $M = \{0\text{kg}, 1\text{kg}, 2\text{kg}, 3\text{kg}\}$;
 - ▶ $0\text{kg} < 1\text{kg} < 2\text{kg} < 3\text{kg}$;
- $\alpha: R \rightarrow M$ is a one-to-one function that conventionally assigns to each object in R a symbol in M : $\alpha(r_n) = n\text{kg}$



13 Calibration


MS $\langle m, \mathcal{E}, \kappa, \mathcal{S}, \lambda \rangle$ is calibrated w.r.t mST $\langle R, \mathcal{R}, \alpha \rangle$ iff:

- ▶ $\mathcal{S} = \mathcal{R}$ (or more generally, there is a one-to-one relation between \mathcal{S} and \mathcal{R} , i.e. the MS resolves the reference objects of the mST);
- ▶ for each $r, r_1, \dots, r_n \in R$
 - ▶ $\lambda(\kappa(r)) = \alpha(r)$ and
 - ▶ $S_i(\lambda(\kappa(r_1)), \dots, \lambda(\kappa(r_n)))$ iff $S_i^M(\alpha(r_1), \dots, \alpha(r_n))$



14 Measurement framework

- A **measurement framework** is a couple $\langle s, M^* \rangle$ where s is an mST, and M^* is a set of MSs calibrated with respect to s .
- Abstract from the physical implementation/relatization of the MSs




15 a has P

- Given an mST s with symbolic structure $\langle M, S_1^M, \dots, S_n^M \rangle$, it is possible to **associate** to each $s_p \in M$ a property P :

' a has P ' if and only if there exists an MS $\langle m, \mathcal{E}, \kappa, \mathcal{S}, \lambda \rangle$ calibrated with respect to s such that $\lambda(\kappa(a)) = s_p$

- e.g. a has the property of 'being 2kg heavy' iff $\lambda(\kappa(a)) = 2\text{kg}$:




16 a has P at t

- Given an mST s with symbolic structure $\langle M, S_1^M, \dots, S_n^M \rangle$, it is possible to **associate** to each $s_p \in M$ a property P :

' a has P at t ' if and only if there exists an MS $\langle m, \mathcal{E}, \kappa, \mathcal{S}, \lambda \rangle$ calibrated (at t) w.r.t. s such that $[t](\lambda(\kappa(a))) = s_p$ (that represents the fact that m and a interacted at t with the result s_p).

- at t a has the property of 'being 2kg heavy' iff $[t](\lambda(\kappa(a))) = 2\text{kg}$:



17 Measurement structure

A measurement structure, is a structure $\langle O, T, S, F \rangle$ where:

- O is a set of 'objects'
- T is a set of 'times'
- S is a set of 'symbols'
- F is a set of *measurement frameworks*

18 The general framework in terms of MSs

Given the measurement structure $\langle O, T, S, F \rangle$:

Objects	$\mathbf{ob}^{\mathcal{I}} \subseteq O$
Times	$\mathbf{tm}^{\mathcal{I}} \subseteq T$
Regions of space i	$\mathbf{sp}_i^{\mathcal{I}} \subseteq M_i$ (the set of symbols of the mST s_i in an MF of F)
Location	$\mathbf{L}^{\mathcal{I}} \subseteq S \times O \times T$ and $\langle r, o, t \rangle \in \mathbf{L}^{\mathcal{I}}$ iff there exists an MS $\langle m, \mathcal{E}, \kappa, \mathcal{S}, \lambda \rangle$ belonging to some M_i^* (in one measurement framework) such that $[t](\lambda(\kappa(o))) = r$

19 Classification as measurement

- $\text{EX}(o, t') \wedge \text{L}(r, o, t) \wedge \text{sp}_i(r) \rightarrow \exists r'(\text{L}(r', o, t') \wedge \text{sp}_i(r'))$
if, at a given time t , an object o is located in a specific space sp_i , then it is located in sp_i at every time at which o exists.
- Seems ontologically but not empirically plausible: the fact that o has been measured at t does not imply that o has been measured (w.r.t. the same dimension sp_i) at every time at which it exists.
- Objects can be classified and compared only by measuring them.
- It is possible to introduce a potential aspect, i.e. if measured an object would produce a specific result, but this seems to require the difficult notion of *disposition*.

20 Measurement and realism

- Objects that interact with the support providing the same result ($\kappa(o) = \kappa(o')$) can, but do not necessarily need to, share an *ontological/physical* property.
 - ▶ In particular an MS with a coarse resolution is unable to distinguish some ontological properties.
- On the other hand, the states induced in the MS depend on the ontological properties of the objects.
 - ▶ MSs are **built** because the classifications and the comparisons they provide allow us for (environmentally useful) **predictions**.
- Calibration and symbolization assure *inter-subjectivity* and *communicability*.

21 Change of mSTs and MSs

- **mSTs can change across time**

A property is associated to a symbol of an mST that identifies a reference object. The diachronic alignment of the MSs relies on the calibration, at different times, w.r.t. **the same** mST. The change of reference objects of an mST invalidates the alignment.

- **MSs can change across time**

Interaction and symbolization functions depend on the structure of the support m that can change across time. By (diachronically) calibrating an MS m w.r.t a stable mST s one assures the stability of m . Even assuming instantaneous measurement: (i) MSs are not re-calibrated every time they are used, and (ii) calibration and measurement cannot be synchronous.

22 Stable frameworks of objects

- If mSTs and MSs are **assumed** to be stable (at least from the calibration to the measurement), the state of $m \bullet a$ and the one of $m \bullet b$ depend exclusively on how a and b are.
- Only by assuming the stability of a framework of objects (mST and MSs) one can conclude that a and b *share* a property, that a *similarity* between them exists.
- Instead of re-identifying objects on the basis of a stable framework of properties, here we are 're-identifying properties' on the basis of a stable framework of objects.

23 Infinite regression

- **But** to empirically justify the stability of mSTs and MSs one needs to diachronically compare the supports and reference objects.
- To do that other mSTs and MSs, the stability of which, in turn, needs to be justified.

Infinite regression! (or circularity)

- One can consider the *global framework* of all mSTs and MSs, the stability of which is determined on the basis of the **mutual relationships** between the components.
- This does not detect absolute change that maintain the mutual relationships.

24 Sensory systems

- Is it possible to establish a parallel between sensory systems and measurement systems?
- Is it possible to provide a more sensory oriented interpretation of the previous general framework re-using what we have done for measurement systems?
- How distal stimuli are compared or classed together? Is it still possible to avoid powerful assumptions about their conformity with external kinds/ontological properties?

25 Matthen's sensory classification thesis

- (I.a) Sensory systems classify and categorize; they sort and assign distal stimuli to classes [different from Sense Datum Theory].
- (I.b) Ideally they do so on some consistent basis.
- (I.c) The result of this activity have a lasting effect on the perceiver in the form of conscious memories (...).
- (II) A *sense-feature* is a property a stimulus appears to have by virtue of an act of sensory classification.
 - ▶ *Colours* are the properties **distal stimuli** appear to have when colour vision assigns them to classes.
 - ▶ Sensory systems create classificatory categories for the use of the organism of which they are a part.

26 Matthen's 3 stages sensory process (a)

- **Stimuli:** material objects and the packets of energy that they send to our sensory receptors.
- **Sensory classes:** the groups that the system makes of the stimuli, and sense-features, the properties that stimuli in a given sensory class share in virtue of belonging to that class.
 - ▶ Sensory classes can group physically different stimuli and their structure can mismatch the physical structure of stimuli: classification is useful for the acting and survival of species.
- **Sensations** (phenomenal or sensory experiences): the consciously available record of sensory classification, a label that identifies a distal stimulus as belonging to a particular class.
 - ▶ Classification is available not only to consciousness.

27 Matthen's 3 stages sensory process (b)

- The function of sensory experience is to provide us *access* to sensory classification for purposes of reasoning (and beliefs' formation).
- Through sensations, we come to know of distal objects that have been classified a certain way (awareness of external objects).
- Discriminability/indiscriminability of stimuli in sensory experience of them is a consequence of how sensory systems classify them.
- Sensation is how we come to know that our sensory systems have assigned a stimulus to a particular class.
- Sensation is the indicator, not the constitutive characteristic, of sensory classification.
- **First classification, then sensory appearance as label.**

28 Dretske: phenomenal vs. conceptual awareness

- Sensory experiences are different from knowledge, beliefs, judgments, etc.: *a child or an animal might be visually aware of the shirt's color without their knowing or thinking that the shirt is blue, without being conscious that anything is blue.*
- Two speedometers that have the same 'experience' (viz. of an axle rotation of N rpm) could give rise to different 'beliefs' (about speed, because the diameter of the connected wheels differs).
- Through learning, I can change what I believe when I see k , but I can't much change the way k looks (phenomenally) to me (...) We can, through learning, change our calibration.
- Experiences are states whose repr. properties are *systemic*, thoughts are states whose repr. properties are *acquired*.

29 The problem of objects

- When I have a red experience, do I have an experience of an object classified as red, or do I have the experience without any specific subject?
 - Measurement theories assume a set of objects and the interaction function. What happens if I have access only to the internal states of the instrument (I don't see/know what I'm measuring)?
 - Is this parallel correct?
-
- ▶ Link with *foci of attention*.
 - ▶ Link with Pylyshyn's theory.

30 Auto-calibration

How the symbolization function can be established?

- Suppose to find an instrument without any symbol on it.
- Suppose to know how the instrument can interact with the environment and to discern its internal states.
- Suppose to write symbols in correspondence of internal states.
- Then, assuming the stability of the instrument, one can **compare** and **classify** objects.
- Without understanding what she is measuring, she can observe that objects of kind A are 'good' while objects of kind B are 'bad'.
- Then, one starts to do some predictions on the environment.